

2.10.6.2 Sample preparation and preliminary inspection

Three sample boards (or, for 2.10.9, two components and one board) identified as samples 1, 2 and 3 are required. It is permitted to use either actual boards or specially produced samples with representative coating and minimum separations. Each sample board shall be representative of the minimum separations used, and coated. Each sample is subjected to the full sequence of manufacturing processes, including soldering and cleaning, to which it is normally subjected during equipment assembly.

When visually inspected, the boards shall show no evidence of pinholes or bubbles in the coating or breakthrough of conductive tracks at corners.

Table 2N – Minimum separation distances for coated printed boards

| WORKING VOLTAGE | | | FUNCTIONAL, BASIC or SUPPLEMENTARY INSULATION | REINFORCED INSULATION |
|------------------|----------------------------|--------|--|--------------------------|
| V r.m.s. or d.c. | | | mm | mm |
| | up to and including | 63 | 0,1 | 0,2 |
| Over | 63 up to and including | 125 | 0,2 | 0,4 |
| Over | 125 up to and including | 160 | 0,3 | 0,6 |
| Over | 160 up to and including | 200 | 0,4 | 0,8 |
| Over | 200 up to and including | 250 | 0,6 | 1,2 |
| Over | 250 up to and including | 320 | 0,8 | 1,6 |
| Over | 320 up to and including | 400 | 1,0 | 2,0 |
| Over | 400 up to and including | 500 | 1,3 | 2,6 |
| Over | 500 up to and including | 630 | 1,8 | 3,6 |
| Over | 630 up to and including | 800 | 2,4 | 3,8 |
| Over | 800 up to and including | 1 000 | 2,8 | 4,0 |
| Over | 1 000 up to and including | 1 250 | 3,4 | 4,2 |
| Over | 1 250 up to and including | 1 600 | 4,1 | 4,6 |
| Over | 1 600 up to and including | 2 000 | 5,0 | 5,0 |
| Over | 2 000 up to and including | 2 500 | 6,3 | 6,3 |
| Over | 2 500 up to and including | 3 200 | 8,2 | 8,2 |
| Over | 3 200 up to and including | 4 000 | 10 | 10 |
| Over | 4 000 up to and including | 5 000 | 13 | 13 |
| Over | 5 000 up to and including | 6 300 | 16 | 16 |
| Over | 6 300 up to and including | 8 000 | 20 | 20 |
| Over | 8 000 up to and including | 10 000 | 26 | 26 |
| Over | 10 000 up to and including | 12 500 | 33 | 33 |
| Over | 12 500 up to and including | 16 000 | 43 | 43 |
| Over | 16 000 up to and including | 20 000 | 55 | 55 |
| Over | 20 000 up to and including | 25 000 | 70 | 70 |
| Over | 25 000 up to and including | 30 000 | 86 | 86 |

For voltages between 2 000 V and 30 000 V linear interpolation is permitted between the nearest two points, the calculated spacing being rounded up to the next higher 0,1 mm increment.