

GFCI Right Angle Cord Sets

Ideal for use by contractors and industrial maintenance personnel working with extension cords or portable tools. Provides compliance with National Electric Code (NEC) Article 527.6 for "Temporary Wiring". Applications include:

- ▶ High Pressure Sprayer Washers
- ▶ Drain Snakes
- ▶ Construction Sites
- ▶ Power Tools
- ▶ Pumps
- ▶ Industrial Appliances

Rainproof rated, UL listed for outdoor use. Standard lengths: 9', 6', 25', 50'.

Custom cable gauges, lengths and terminations available by special order. To prevent unmonitored equipment startup, manual reset is required after GFCI trip and power outage. Available with yellow or black case.

FEATURES

Model 14880-4 ⓘ

- ▶ Volts/Amps: 120V/15A
- ▶ Cord Gauge: 14/3 AWG.
- ▶ NEMA 5 - 15 P & R
- ▶ Trip Level: 4 - 6 mA

Model 14880-2 ⓘ

- ▶ Volts/Amps: 120V/15A
- ▶ Cord Gauge: 12/3 AWG.
- ▶ NEMA 5 - 15 P & R
- ▶ Trip Level: 4 - 6 mA



TECHNICAL DATA

Grounded neutral	4 Ohms typical
Trip response time for ground fault and grounded neutral trip	less than 25mS
Voltage surge withstand (MOV Protection)	3kv ringwave test and 4kv/2kA surge immunity test
Radio frequency noise susceptibility	operates within normal limits with 0.5 volts injected on power line 150-230 mHz
Frequency	50 / 60 Hz
Endurance	3,000 operations minimum
Overload Current	six times rated current
Operating temperature range	-35 °C to 66 °C
Effect of 10 Amp turn DC Shock on ground fault trip	5% maximum trip level variation
Insulation voltage	1500 VRMS - 1 Min.
Power On indication	mechanical indicator

