


小信号肖特基二极管 Small Signal Schottky Diodes

**特征 Features**

- 反向漏电流小。Low reverse leakage
- 开关速度快。Fast switching speed
- 最大功率耗散500mW。Maximum power dissipation 500mW
- 高稳定性和可靠性。High stability and high reliability

机械数据 Mechanical Data

封装: DO-35 玻璃封装 Case: DO-35 Glass Case

极性: 色环端为负极 Polarity: Color band denotes cathode end

安装位置: 任意 Mounting Position: Any

极限值和温度特性 TA = 25°C 除非另有规定。

Maximum Ratings & Thermal Characteristics Ratings at 25°C ambient temperature unless otherwise specified.

	符号 Symbols	1N4148	1N4448	单位 Unit
不重复峰值反向电压 Non-repetitive Peak Reverse Voltage	V _{RM}	100		V
反向峰值电压 peak repetitive Reverse Voltage	V _{RRM}	75		V
最大正向平均电流 Forward Continuous Current	I _{FM}	300	500	mA
平均整流输出电流 Average Rectified Output Current	I _O	150		mA
正向(不重复)浪涌电流 Non-Repetitive Peak Forward Surge Current	I _{FSM}	2.0		A
功率消耗 Power Dissipation	P _d	500		mW
典型热阻 Type Thermal Resistance	R _{θJA}	300		K/W
工作结温和存储温度 Operating junction and storage temperature range	T _j , T _{STG}	-50 --- +150		°C

电特性 TA = 25°C 除非另有规定。

Electrical Characteristics Ratings at 25°C ambient temperature unless otherwise specified.

	符号 Symbols	最小值 MIN.	最大值 MAX.	单位 Unit	测试条件 Test Condition
正向电压 Forward voltage 1N4148 1N4448 1N4448	V _{FM}	---	1.0	V	I _F = 10mA
		0.62	0.72		I _F = 5.0mA
		---	1.0		I _F = 100mA
反向电流 Reverse current Reverse current	I _{RM}	---	5.0	μA	V _R = 75V
			50		V _R = 70V, T _j = 150°C
			30		V _R = 20V, T _j = 150°C
			25		V _R = 20V
结电容 Junction capacitance	C _j	---		pF	V _R = 0, f = 1.0MHz
反向恢复时间 Reverse Recovery Time	trr	---	4.0	nS	I _F = 10mA — I _R = 1.0mA V _R = 6.0V, R _L = 100Ω

特性曲线 Characteristic Curves

